



DispenserONE® MAXI is a very high capacity dispenser of sanitizing chemicals, designed to be installed in very big facilities such as international airports, hospitals, superstores and any other high traffic areas.

Its high capacity leads to a reduced maintenance helping to minimize tanks filling operational costs and service interruptions.

MODELS:

- DispenserONE® MAXI 50 Liters 100÷240 Vac

KEY FEATURES and BENEFITS

- High tank capacity allows more than 50.000 doses of sanitizing gel in average, minimizing the servicing due to tanks refilling/replacement, especially in places with high influx of people.
- Two pump design allows managing two different tanks thus prevents unplanned downtime by switching automatically from one tank to another when the first is empty.
- Touch free dispensing through proximity sensor guarantees maximum hygiene and safety.
- Peristaltic dosing with single shot fine adjustment ensures maximum dosage accuracy and repeatability.
- Stepper motor technology guarantees the maximum reliability and lifespan.
- Single dose quantity can be adjusted via smartphone for a maximum flexibility according to the different chemical dispensed.
- A calibration of the pumps can be executed via wi-fi connection to ensure the accuracy of dosage.
- Integrated level control gives direct warnings to the owner avoiding lack of disinfectant in the device.
- Wi-Fi accessibility of the device via smartphone or tablet provides information on the total number of dispensed doses, the total dispensed chemical, the remaining chemical in the tank, the general status of the unit.
- “Push” alarm messages can be sent by the unit via e-mail to the owner to alert on different issues like chemical level, tube replacement or others, allowing prompt maintenance interventions.
- Its very robust design, makes it suitable to high traffic facilities.

TECHNICAL FEATURES	
TYPE	DispenserONE® MAXI
CERTIFICATIONS	CE, EAC
MAXIMUM TANK CAPACITY	50 liters
MINIMUM CANISTER OPENING	32 mm
DISPENSING RATE	Adjustable 0,2 to 2,0 ml
POWER SUPPLY	100÷240 Vac @50/60 Hz
ELECTRICAL CLASS	Class I (ground connected)
ACTIVATION	Touch free via proximity sensor
MAX CONSUMPTION	50 W
OPERATING TEMPERATURE	10-50°C
STORAGE TEMPERATURE	-20÷60°C
CASE MATERIAL	Zinc plated Iron
MAX UNITS PER PALLET	4

DIMENSIONS

